

[Products](#) > [Pipe bend](#) > Glass pipe bend

GLASS PIPE BEND

FACTS

- + Material: Borosilicate glass 3.3
- + With 5 mm wall thickness
/ for stainless steel pipe 40 / 50 / 60.3 / 76.1 mm
- + With bonded copper band



Ø 47,0

Ø 48,3

Ø 56,0

Ø 66,0

Ø 80,0

Ø47.0 (40.0) X 5.0 mm

Article no.	Angle [°]	Radius [mm]	SV1 [mm]	SV2 [mm]
RBG-047050-90100-1010	90	100	100	100
RBG-047050-45100-1010	45	100	100	100
RBG-047050-90250-2020	90	250	200	200
RBG-047050-45250-2020	45	250	200	200
RBG-047050-90500-2020	90	500	200	200
RBG-047050-45500-2020	45	500	200	200

Ø48.3 (45.0) X 3.2 mm

Article no.	Angle [°]	Radius [mm]	SV1 [mm]	SV2 [mm]
RBG-048332-90100-1010	90	100	100	100
RBG-048332-45100-1010	45	100	100	100
RBG-048332-90300-2020	90	300	200	200
RBG-048332-45300-2020	45	300	200	200
RBG-048332-90500-2020	90	500	200	200
RBG-048332-45500-2020	45	500	200	200

Ø56.0 (50.0) X 5.0 mm

Article no.	Angle [°]	Radius [mm]	SV1 [mm]	SV2 [mm]
RBG-056050-90100-1010	90	100	100	100
RBG-056050-45100-1010	45	100	100	100
RBG-056050-90250-2020	90	250	200	200
RBG-056050-45250-2020	45	250	200	200
RBG-056050-90500-2020	90	500	200	200
RBG-056050-45500-2020	50	500	200	200



Ø66.0 (60.3) X 5.0 mm

Article no.	Angle [°]	Radius [mm]	SV1 [mm]	SV2 [mm]
RBG-066050-90120-1515	90	120	150	150
RBG-066050-45120-1515	45	120	150	150
RBG-066050-90250-2020	90	250	200	200
RBG-066050-45250-2020	45	250	200	200
RBG-066050-90500-2020	90	500	200	200
RBG-066050-45500-2020	45	500	200	200

Ø80.0 (76.1) X 5.0 mm


Article no.	Angle [°]	Radius [mm]	SV1 [mm]	SV2 [mm]
RBG-080050-90150-2020	90	150	200	200
RBG-080050-45150-2020	45	150	200	200
RBG-080050-90250-2020	90	250	200	200
RBG-080050-45250-2020	45	250	200	200
RBG-080050-90500-2020	90	500	200	200
RBG-080050-45500-2020	45	500	200	200

PRODUCT DESCRIPTION

Glass tube bends are the wear protection in the plastics industry. For decades, glass tubes and glass tube bends have been used extremely successfully with polyamide and glass fibre reinforced plastics to minimize wear and thus downtimes.

Glass tube bends from Michel Tube have a wall thickness of 5 mm and have a consistent hardness on this wall thickness. It is important to know that the inside diameter must be aligned, which is why all Michel Tube glass elbows are specially manufactured for this purpose. For the connection with the stainless steel tube, so-called glass tube connectors are used, which connect two different outer diameters (glass and stainless steel). A copper strip is attached to the outside to ensure electrical conductivity.

PICTURE GALLERY





Michel Tube Engineering GmbH

Industriepark A81
Falk-Müller-Straße 30
97941 Tauberbischofsheim

info@michel-tube.com

Tel.: +49 9341 848 550-0
Fax: +49 9341 848 550-5



Products

Round tubes	Pipe bend
Tube fittings	Pipe connector
Pipe couplings	Hose lines
Hose couplings	Coded labeling
Material distributor	Suction lances
Magnetic separator	System components

Industries

The company

Catalog

Contact us

